

## Detailed Specifications



WorkCentre 5632 shown with Duplex Automatic Document Feeder, High Capacity Tandem Tray and Offset Catch Tray



WorkCentre 5638 shown with Duplex Automatic Document Feeder, High Capacity Tandem Tray and Basic Office Finisher



WorkCentre 5645 shown with Duplex Automatic Document Feeder, High Capacity Tandem Tray and Office Finisher



WorkCentre 5655 shown with Duplex Automatic Document Feeder, High Capacity Tandem Tray, High Capacity Feeder and High Volume Finisher

### WorkCentre 5632/5638

### WorkCentre 5645/5655

#### OUTPUT SPEED – printing and copying

Up to 32 and 38 ipm (images per minute)  
8.5 x 11 in. (A4/210 x 297 mm)

Up to 45 and 55 ipm (images per minute)  
8.5 x 11 in. (A4/210 x 297 mm)

Up to 25 ipm  
8.5 x 14 in. (216 x 356 mm)

Up to 36 ipm  
8.5 x 14 in. (216 x 356 mm)

Up to 22 ipm  
11 x 17 in. (A3/297 x 420 mm)

Up to 31 ipm  
11 x 17 in. (A3/297 x 420 mm)

#### FIRST-IMAGE-OUT TIME (FCOT) – letter size, from platen to offset catch tray

As fast as 4.6 seconds

As fast as 3.4 seconds

### Copy Specifications

#### COPYING

<b>Document Scanner</b>	Platen (available with WorkCentre 5632/5638) or Duplex Automatic Document Handler (DADH) option (Standard with WorkCentre 5638/5645/5655). Scans sizes up to 11 x 17 in. (A3/297 x 420 mm) SEF
<b>Sides (input:output)</b>	1:1, 1:2, 2:2 and 2:1
<b>Quantity</b>	1 to 9,999
<b>Resolution</b>	600 x 600 x 8 bit dpi input / 4800 x 600 dpi interpolated output
<b>Concurrency*</b>	Unlimited program-ahead consistent with configuration (Copy, Print, Fax and Scan)
<b>Copy Pre-Collation Memory (EPC)</b>	128 MB — Copier (expandable to 512 MB) 384 MB — Copier/Printer (expandable to 512 MB)

Continued

\* A minimum of 256 MB EPC memory required

## Copy Specifications

## COPYING (Continued)

<b>Basic Copy Features/Options</b>	<b>Features</b>	<b>Options</b>
	Collation Automatic 2-Sided/Duplex Auto Reduction and Enlargement to fit selected paper size Auto Paper Select Auto Tray Switching	Hole Punching Stapling Booklet Creation
<b>Imaging Copy Features</b>	Image Quality <ul style="list-style-type: none"> <li>• Original Type Selections: Normal, Text, Halftone, Photo</li> <li>• Output Quality Selections: Lighter/Darker, Background Suppression, Contrast, Sharpness or Screening</li> </ul> Book Copying/Bound Copying Edge Erase (with Print to Edge option) Mixed Size Original Image Shift (with Auto Center option)	
<b>Output Copy Features</b>	ID Card Copy Booklet Creation Inserts and Tab copying Covers (Front only, Front and Back, Back only: Blank or Printed) Build Job (Enables page-level programming to include tab copying and also lets you proof each section or delete last section as the job is built) Annotation and Bates Stamping Multi-up (up to six columns by six rows) Invert Image (negative or mirror image) Sample Set and Job Storage (Store and Recall job programming) Transparencies (including dividers – blank or printed) Heavy weight paper (not rough stock)	
<b>Other Copy/Device Features</b>	Job Interrupt (Interrupt the current job) Help (Intuitive text and graphic descriptions) Internal Auditron (Copy) Languages (Select up to 21 languages for User Interface – US English, International English, International French, Italian, German, International Spanish, Catalan, Dutch, Portuguese, Brazilian [Latin Portuguese], Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian)*	
<b>Reduction/Enlargement</b>	Variable Zoom from 25% - 400% in 1% increments Six User-Programmable percentages (25%, 64%, 78%, 129%, 154% and 200%)	
<b>Foreign Device Interface (FDI) (Optional)</b>	Interface to third-party access control devices, coin machines, card readers Supports a variety of vending stations available through the Xerox Custom Application Service	
<b>USB Port</b>	PC interface for upload/download of internal auditron data and Xerox Copier Assistant Customer device administration/software upgrade	

*Continued*  
\*Language selection and number varies by location.

## Copy Specifications

**COPYING** (Continued)

**Accessibility Option** Xerox Copier Assistant (XCA) Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.

**PAPER HANDLING – Duplex Automatic Document Feeder (DADF) (optional with 5632 configurations)**

<b>Capacity*</b>	WorkCentre 5632/5638: 75 sheets WorkCentre 5645/5655: 100 sheets
<b>Speed</b>	Up to 60 ipm (images per minute) simplex / up to 28 ipm duplex, 8.5 x 11 in. (A4/210 x 297 mm) long edge feed (LEF)
<b>Paper Sizes Sensed</b>	Statement – 5.5 x 8.5 in. (A5/148 x 210 mm long edge feed (LEF) or short edge feed (SEF) Letter – 8.5 x 11 in. (A4/210 x 297 mm) LEF or SEF Legal – 8.5 x 14 in. (216 x 356 mm) SEF Ledger – 11 x 17 in. (A3/297 x 420 mm) SEF
<b>Weights</b>	13 lb to 32 lb bond (50 to 120 gsm)

**PAPER HANDLING – Two Front Loading Paper Trays**

<b>Capacity*</b>	500 sheets each
<b>Sizes</b>	User adjustable from 5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)
<b>Weights</b>	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)
<b>Types</b>	Letterhead Preprinted forms Plain Paper Drilled/Hole-punched Heavyweight Recycled Tab Stock Bond Envelopes Custom Settings (up to 7)
<b>Options</b>	Envelope Tray Kit for Tray 2 (Capacity 50 envelopes)

**PAPER HANDLING – Bypass Tray**

<b>Capacity*</b>	100 sheets
<b>Sizes</b>	User Adjustable from 4.13 x 5.83 in. (105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
<b>Weights</b>	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)

Continued

\*Paper capacities are based on 20 lb bond stock; capacities will vary with different weight stocks.

## Copy Specifications

**PAPER HANDLING – Bypass Tray (Continued)**

<b>Types</b>	Letterhead Preprinted forms Plain Paper Drilled/Hole-punched Heavyweight Recycled Label Stock Transparencies Tab Stock Bond Envelopes Custom Settings (up to 7)
--------------	--

**PAPER HANDLING – High Capacity Tandem Tray (Optional with WorkCentre 5632, 5638, 5645; Standard on 5655)**

<b>Capacity*</b>	Two trays: 1,600 and 2,000 sheets
<b>Sizes</b>	8.5 x 11 in. (A4/210 x 297 mm) LEF
<b>Weights</b>	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)

**PAPER HANDLING – Tray 5 High Capacity Feeder (optional)**

<b>Capacity*</b>	4,000 sheets
<b>Sizes</b>	8.5 x 11 in. (A4/210 x 297 mm) LEF Optional 8.5 x 11/8.5 x 14 Short Edge Kit – 8.5 x 14 in. (A4/210 x 297 mm) SEF with 2,000 sheet capacity Optional 11 x 17 Short Edge Kit – 11 x 17 in. (A3/297 x 420 mm) SEF with 2,000 sheet capacity
<b>Weights</b>	16 lb to 53 lb bond/120 lb index (60 to 216 gsm)

**PAPER HANDLING – Total Capacity**

<b>Device Total Capacity*</b>	8,700 sheets (with Bypass tray, front loading paper trays, High Capacity Tandem Tray and High Capacity Feeder)
-------------------------------	--

**OUTPUT OPTION – Offset Catch Tray (OCT) option**

<b>Capacity*</b>	300 sheets
<b>Sizes</b>	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
<b>Weights</b>	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)

**OUTPUT OPTION – Basic Office Finisher option (available for 5632, 5638 and 5645 only)**

<b>Capacity*</b>	Top Tray — 250 sheets Stacking Tray — 1,000 sheets
<b>Sizes</b>	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
<b>Weights</b>	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)
<b>Stapling*</b>	30 sheets Single position (top right hand corner)

Continued

\*Paper capacities are based on 20 lb bond stock; capacities will vary with different weight stocks.

## Copy Specifications

## OUTPUT OPTION – Office Finisher option

<b>Capacity*</b>	Top Tray — 250 sheets Stacking Tray — 2,000 sheets	
<b>Sizes</b>	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)	
<b>Weights</b>	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)	
<b>Stapling*</b>	50 sheets Single (any corner) and dual	
<b>Hole Punch (Optional)</b>	<b>North America</b>	<b>Europe</b>
	3-hole punch	2-hole punch
	2-hole Legal punch	4-hole punch
		4-hole “Swedish” punch

## OUTPUT OPTION – Professional Finisher option (available for 5632, 5638 and 5645 only)

<b>Capacity*</b>	Top Tray — 250 sheets Stacking Tray — 1,500 sheets	
<b>Sizes</b>	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)	
<b>Weights</b>	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)	
<b>Stapling*</b>	50 sheets Single (any corner), dual, front, rear, SEF and 4-stitch	
<b>Hole Punch (Standard)</b>	<b>North America</b>	<b>Europe</b>
	3-hole punch	2-hole punch
<b>Hole Punch (Optional)</b>	2-hole Legal punch	4-hole punch
		4-hole “Swedish” punch
<b>Booklet Maker</b>	<b>Capacity*</b> <ul style="list-style-type: none"> <li>• Tray stop up: 30 booklets (1-15 sheets per booklet)</li> <li>• Tray stop down: Unlimited</li> </ul>	
	<b>Sizes</b> <ul style="list-style-type: none"> <li>• Letter — 8.5 x 11 in. (A4/210 x 297 mm)</li> <li>• Legal — 8.5 x 14 in. (216 x 356 mm)</li> <li>• Ledger — 11 x 17 in. (A3/297 x 420 mm)</li> </ul>	
	<b>Weights</b> <ul style="list-style-type: none"> <li>• 16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)</li> </ul>	
	<b>Stapling*</b> <ul style="list-style-type: none"> <li>• Saddle-stitch (2-15 sheets / 8-60 page booklet)</li> </ul>	
	<b>Folding</b> <ul style="list-style-type: none"> <li>• V-folding (1-15 sheets / unstapled)</li> </ul>	

*Continued*  
\*Paper capacities are based on 20 lb bond stock; capacities will vary with different weight stocks.

## Copy Specifications

## OUTPUT OPTION – High Volume Finisher Option (available for 5655 only)

<b>Capacity*</b>	Top Tray — 250 sheets Stacking Tray — 3,000 sheets	
<b>Sizes</b>	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)	
<b>Weights</b>	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)	
<b>Stapling*</b>	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch	
<b>Hole Punch (optional)</b>	<b>North America</b>	<b>Europe</b>
	Option 1 — 3-hole punch	2-hole punch
	Option 2 — 2-hole Legal punch	4-hole punch 4-hole “Swedish” punch

## OUTPUT OPTION – High Volume Finisher with Booklet Maker option (available for 5655 only)

<b>High Volume Finisher with Booklet Maker option</b>	<b>Capacity*</b>	Top Tray — 250 sheets Stacking Tray — 3,000 sheets	
	<b>Sizes</b>	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)	
	<b>Weights</b>	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)	
	<b>Stapling*</b>	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch	
	<b>Hole Punch (optional)</b>	<b>North America</b>	<b>Europe</b>
	Option 1 — 3-hole punch	2-hole punch	
	Option 2 — 2-hole Legal punch	4-hole punch and 4-hole “Swedish” punch	
<b>Booklet Maker</b>	<b>Capacity*</b>	<ul style="list-style-type: none"> <li>• Tray stop up: 30 booklets (1-15 sheets per booklet)</li> <li>• Tray stop down: Unlimited</li> </ul>	

Continued

\*Paper capacities are based on 20 lb bond stock; capacities will vary with different weight stocks.

## Copy Specifications

**OUTPUT OPTION – High Volume Finisher with Booklet Maker option** *(continued)**Sizes*

- Letter — 8.5 x 11 in. (A4/210 x 297 mm)
- Legal — 8.5 x 14 in. (216 x 356 mm)
- Ledger — 11 x 17 in. (A3/297 x 420 mm)

*Weights*

- 16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)

*Stapling\**

- Saddle-stitch (2-15 sheets / 8-60 page booklet)

*Folding*

- V-folding (1-15 sheets / unstapled)

**OUTPUT OPTION – Z-Fold / C-Fold Unit with HVF with Booklet Maker option****Z-Fold / C-Fold unit***Capacity\**

- 50 sheets or unlimited capacity with tray stop in the down position

*Sizes*

- Letter — 8.5 x 11 in. (A4/210 x 297 mm)

*Weights*

- 16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)

**OUTPUT OPTION – Post Process Inserter (optional with HVF and HVF with Booklet Maker)****Post process Inserter  
(optional with HVF with  
Booklet Maker)***Capacity\**

- 250 sheets
- Tray stop down: Unlimited

*Sizes*

- Letter — 8.5 x 11 in. (A4/210 x 297 mm)
- Legal — 8.5 x 14 in. (216 x 356 mm)
- Ledger — 11 x 17 in. (A3/297 x 420 mm)

*Weights*

- 16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)

**OUTPUT OPTION – Convenience Stapler option****Capacity\***

50 sheets

\*Paper capacities are based on 20 lb bond stock; capacities will vary with different weight stocks.

## Print Specifications

### NETWORK PRINTING – Smart Controller (*Simultaneous rip, receive, program ahead, queue processing, and transmit*)

<b>Processor</b>	1.4 GHz AMD Athlon dedicated
<b>Memory (ESS)</b>	256 MB
<b>System Disk</b>	80 GB Hard Drive shared
<b>Printer Language (PDL) auto switching</b>	<ul style="list-style-type: none"> <li>• PCL 6/PCL 5e</li> <li>• PostScript 3 emulation</li> <li>• TIFF (6.0 Old JPEG and New JPEG)</li> <li>• TIFF Fax Extended (TIFF - FX)</li> <li>• PDF</li> <li>• LCDS, SCS, XES and IPDS through third party transforms</li> </ul>

### NETWORK PRINTING – Resolution (*printing via CentreWare software*)

PostScript emulation: 600 x 600 dpi and 1200 x 1200 dpi (up to 256 shades of grey)  
 PCL: 600 x 600 dpi  
 Supports PCL and PS switching within job

<b>Advanced Features Include</b>	Bi-directional Print Drivers Embedded web server for remote control/monitor/setup Job monitoring at the device and at desktop
----------------------------------	---

### NETWORK PRINTING – Printing Features

<b>Paper Output</b>	Special font Banner Sheet Rotate Image Offset
---------------------	--

### NETWORK PRINTING – Print Driver Options

Job Type

- Secure, Sample, Delay
- LAN Fax-with fax option
- Save and Save & Print\*

Paper Selection by attribute (including transparency separators)  
 Duplex (2-sided)  
 Finishing

- Multiple Stapling positions
- Hole punch (if configured)
- Booklet creation
- Fit to new paper size
- Saddle stitch with Professional Finisher (5632/5638/5645) and High Volume Finisher Booklet Maker (5655)

Output tray selections  
 Store and recall driver setting

<b>Special Pages</b>	Exception Page programming (covers, inserts/tabs, exception pages)
----------------------	--

Continued

## Print Specifications

## NETWORK PRINTING – Print Driver Options (Continued)

<b>Image Options</b>	Light/Dark Toner saver Resolution options (600 x 600 and 1200 x 1200 dpi) Reduction/Enlargement Margins (edge to edge printing) Invert Image (negative/mirror)
----------------------	---

<b>Layout/Watermark</b>	N-up (16)/Multi-up Booklet Layout/Finishing Fit to new paper size Image orientation Watermark options
-------------------------	---

## PRINT PROTOCOLS AND NETWORKS

<b>Physical</b>	Ethernet 10/100BaseT, 10BaseT, 10Base2(IEEE802.5) (Token ring) –via adapter, wireless Ethernet (IEEE802.11a/b/g) -via third party adapter USB 2.0 / (IEEE1284) Parallel Port Kit (Copier/Printer option)
-----------------	--

<b>Operating Systems</b>	Microsoft Windows 2000, XP, Windows Server XP, Windows Server 2003, Citrix, Novell NetWare 4.x, 5.x, 6 • Mac OS 8.x, 9.x, OS 10.3 • Solaris 2.8, 2.9, 2.10 • HPUX 11.0 • IBM AIX 4.3.3 • Linux Fedora Core 1 (Intel) • Linux Yellowdog 3.0
--------------------------	--

<b>Network Protocols</b>	• TCP/IPv4/IPv6, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX and Net BEUI, IPP • AppleTalk/EtherTalk
--------------------------	---

<b>Administration Protocols</b>	DHCP, BOOTP, SNMP, WINS, Bonjour, DDNS, SLP v2, SSDP, HTTP/S, RARP, LDAP, SMTP, POP3
---------------------------------	--

<b>Security Protocols/Features</b>	<table> <thead> <tr> <th><b>Protocols</b></th> <th><b>Features</b></th> </tr> </thead> <tbody> <tr> <td>• HTTPS</td> <td>• IP filtering</td> </tr> <tr> <td>• IPsec</td> <td>• Unlimited Secure Print</td> </tr> <tr> <td>• 802.1x</td> <td>• Audit log</td> </tr> <tr> <td>• SNMPv3</td> <td>• Image Overwrite</td> </tr> <tr> <td></td> <td>• Data Encryption</td> </tr> </tbody> </table>	<b>Protocols</b>	<b>Features</b>	• HTTPS	• IP filtering	• IPsec	• Unlimited Secure Print	• 802.1x	• Audit log	• SNMPv3	• Image Overwrite		• Data Encryption
<b>Protocols</b>	<b>Features</b>												
• HTTPS	• IP filtering												
• IPsec	• Unlimited Secure Print												
• 802.1x	• Audit log												
• SNMPv3	• Image Overwrite												
	• Data Encryption												

<b>Fonts</b>	PCL: 80 scalable fonts, line printer and bitmap format line printer fonts (true type fonts) PostScript 3: 136 PostScript standard fonts (true type fonts/send fonts as/substitution table) Font Management Utility for downloading additional fonts (available for Windows and Mac)
--------------	---

Continued

## Print Specifications

## PRINT PROTOCOLS AND NETWORKS (Continued)

<b>Print Drivers</b>	<b>Environment</b>	<b>PCL6/5e</b>	<b>PostScript 3</b>
	Windows 2000/XP, Windows Server 2003/2003 64 Bit, Windows Vista/ Vista 64 Bit, Windows Walk-up (PS), Microsoft Certified	Xerox custom graphical user interface Bi-directional features <ul style="list-style-type: none"> <li>• Job, Paper and Toner status</li> <li>• Job status notification</li> <li>• Just in time Bi-Di</li> <li>• Auto population of IP address</li> <li>• Delete jobs</li> </ul>	Xerox custom graphical user interface Bi-directional features <ul style="list-style-type: none"> <li>• Job, Paper and Toner status</li> <li>• Job status notification</li> <li>• Just in time Bi-Di</li> <li>• Auto population of IP address</li> <li>• Delete jobs</li> </ul>
	Macintosh System 8.x – 10.2	N/A	Generic PPD
	Macintosh System 10.3 and higher	N/A	Xerox custom graphical user interface Bi-directional features <ul style="list-style-type: none"> <li>• Toner, Fuser and Xerographic module status</li> </ul>
<b>Print Submission Tools</b>	<b>Environment</b>	<b>PCL PostScript 3</b>	
	Solaris 2.8, 2.9, 2.10; HPUX 11.0, IBM AIX 4.3.3; Linux Fedora Core 1 (Intel); Linux YellowDog 3.0	Submission Tool only	Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)
	TIFF/PDF: Supported in Windows 98/Me/NT 4.0/2000/XP, Windows Server 2003	Submission Tool for any TIFF or PDF file	N/A
<b>DEVICE MANAGEMENT</b>			
<b>Management Support</b>	SNMP Version 1. SNMP Version 2c and SNMP Version 3 MIB access (IETF-MIBII RFC 1213), host resources MIB RFC 2790, Printer MIB RFC v.2		
<b>Xerox CentreWare Internet Services</b>	Allows simple remote installation setting of configuration options and management of the device		
<b>Xerox CentreWare Web</b>	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system. Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP or 2000 (Professional or Advanced Server) Windows 2003 and Internet Explorer 6.0 and higher		
<b>Novell NDPS/NEPS (gateway for WorkCentre)</b>	Server gateway application: centralized management tool		
<b>Xerox CentreWare for Unicenter TNG</b>	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre under a Unicenter TNG Business Process View		
<b>Xerox CentreWare for Tivoli NetView</b>	Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by Tivoli NetView		

Continued

## Print Specifications

**DEVICE MANAGEMENT** (Continued)

<b>Xerox CentreWare for HP OpenView</b>	Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by HP Openview
<b>Xerox Barcode Pro PS (optional)</b> Purchase via <a href="http://www.font.net">www.font.net</a>	Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView  Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.
<b>Xerox Device Types for SAP R/3 Environment are available at</b> <a href="http://www.xerofficesapsolutions.com">www.xerofficesapsolutions.com</a>	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): <ul style="list-style-type: none"> <li>• One- to Two-sided printing</li> <li>• Finishing provides single or dual stapling</li> <li>• Tray pull location from any tray</li> <li>• # of copies – provide the ability to print multiple copies</li> <li>• Paper Type and color – provide ability to select different paper types and paper colors, such as transparency, red, etc.</li> <li>• Print security via PIN ID capability at the WorkCentre</li> <li>• Network Accounting – Provides capability to add Job Based Accounting User IDs to SAP print jobs</li> <li>• Printer banner sheet – Provide the ability to enable/disable printer banner sheets</li> <li>• Barcode printing – Xerox standard PostScript device types available at <a href="http://www.xerofficesapsolutions.com">www.xerofficesapsolutions.com</a> supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at <a href="http://www.font.net">www.font.net</a></li> </ul>
<b>Xerox SAP R/3 Intelligent Barcode Utility (optional)</b> Purchase via <a href="http://www.font.net">www.font.net</a>	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string, and data compression.

**CENTREWARE INTERNET SERVICES – Integrated device Web page**

<b>Device Status</b>	Web server embedded on SMart Controller <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Alerts</li> </ul>
<b>Job-Print Queue Viewing</b>	Complete job print queue management
<b>Job Submission</b>	Print ready files PS, PCL (TIFF, PDF with Copier/Printer only) Output feature selection (2-sided, staple, fold, hole punch, paper select) Delivery options (Immediate, proof, delay and secure)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Scan Template Management</b>	250 templates can be created Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning

Continued

## Print Specifications

## CENTREWARE INTERNET SERVICES – Integrated device Web page (Continued)

<b>Browsers</b>	Netscape 6.2, 7.x (Mozilla 1.x) Internet Explorer 5.5.x, 6.x, 7.x Safari 1.x Mozilla Firefox 1.x
<b>Support</b>	Online support available via web page

## Scan Specifications

## SCANNING

<b>Concurrency</b>	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs
<b>Input Speed</b>	Scan at up to 60 ipm – 8.5 x 11 in. (A4/210 x 297 mm) LEF at all resolutions
<b>Resolutions</b>	<p><i>DPI Options</i></p> <ul style="list-style-type: none"> <li>600 x 600 dpi</li> <li>400 x 400 dpi</li> <li>300 x 300 dpi</li> <li>200 x 200 dpi</li> <li>100 x 100 dpi</li> <li>72 x 72 dpi</li> </ul> <p><i>Scan Presets</i></p> <ul style="list-style-type: none"> <li>• Archival Record (Normal Quality - Smallest file size) – 100 x 100</li> <li>• For Sharing and Printing (Normal Quality - Small file size) – 200 x 200</li> <li>• For High Quality Printing (High Quality - Large file size) – 300 x 300</li> <li>• For OCR (High Quality - Large file size) – 300 x 300</li> <li>• Simple Scan (Normal Quality - Small file size) – 200 x 200</li> </ul> <p><i>Quality/File Size</i></p> <ul style="list-style-type: none"> <li>• Normal Quality (Small file size)</li> <li>• Higher Quality (Large file size)</li> <li>• Maximum Quality (Largest file size)</li> </ul>
<b>Maximum Scan Area</b>	11 x 17 in. (A3/297 x 420 mm)
<b>File Formats</b>	TIFF 6.0 with G3 MH, G4 MMR, MRC or JPEG compression (single page or multiple pages) PDF (image only with G3 MH, G4 MMR, JPEG or JBIG2 compression), PDF/A, XPS, Searchable PDF, PDF/A and XPS Linearized PDF

## SCAN TO EMAIL (Available with the Copier/Printer/Scanner only)

<b>Capability</b>	Scan to e-mail (manual address entry or directory (Exchange/Notes/LDAP) address searching (internal address book or Public address book – up to 128 recipients)
<b>Network Protocol</b>	SMTP MIME encoded
<b>Scan Features</b>	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options

Continued

## Scan Specifications

## NETWORK SCANNING (Available with the Copier/Printer/Scanner only)

<b>Capability</b>	<ul style="list-style-type: none"> <li>• Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare Internet Services</li> <li>• Scan to Home displays one template and populates with the user's directory path after authentication</li> <li>• Scan to file</li> <li>• Scan to network server / directory</li> <li>• Scan to Mailbox*</li> <li>• Scan to Windows XP client via Windows Image Acquisition (WIA) or TWAIN driver downloadable from <a href="http://www.xerox.com">www.xerox.com</a></li> </ul>
<b>Network Protocol</b>	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS
<b>Document Management Fields (Metadata)</b>	<p>Features only available in Network Scan to File Templates:</p> <ul style="list-style-type: none"> <li>• 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template</li> <li>• Metadata Fields consists of field name, display at the LUI or not, default value and other configurations</li> </ul> <p>Customized fields viewed on user interface Variable data entered using virtual keyboard at deviceShare scan templates among WorkCentre via device cloning</p>
<b>Scan Template Management</b>	Scan template management (250 templates) with CentreWare Internet Services Select confirmation sheet option
<b>Scan Features</b>	Build job for Scan to file and Scan to Email (enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass and document feeder), Duplex scanning, Auto detect document size, Scan mixed size originals, scan to edge.

## NETWORK SCANNING SOFTWARE SOLUTIONS

<b>Scan to PC Desktop Workgroup Edition SE V 8.0 (optional)</b>	<p>A desktop offering that provides document imaging, archiving, editing and organization tools</p> <p>ScanSoft PaperPort SE 10 – image viewing and file management software</p> <p>ScanSoft OmniPage SE 4.0 – offer desktop/client installation – OCR and file format conversion software</p> <p>Image Retriever – provides fully automated retrieval of scanned images direct from WorkCentre to individual desktops</p>
<b>Scan to PC Desktop Workgroup Edition Professional V 8.0 (optional)</b>	<p>A desktop offering that provides advanced document imaging, archiving, editing and organization tools.</p> <p>ScanSoft PaperPort Professional 10 image viewing and file management software</p> <ul style="list-style-type: none"> <li>• Complete PDF functionality</li> <li>• Secure PDF workflow of all scanning applications</li> </ul> <p>ScanSoft OmniPage Pro 15 Office (for desktop/client installation) Professional OCR software for digital archiving and document conversion</p> <p>Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes an email inbox polling capability</p>
<b>SMARTsend* (optional)</b>	<p>Server base document routing software that supports multiple scan-enabled multifunctional systems</p> <p>Enables transformation, distribution and routing of scanned documents</p> <p>Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including PDF, workflow settings, workflow summary)</p> <ul style="list-style-type: none"> <li>• Scan to File Destinations: email, Microsoft NetWare folder, network folder, FTP, Microsoft Exchange 2000 web folders, web URL, remote printers</li> <li>• Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint, Hummingbird DNS, Open Text Livelink, Documentum, Interwoven Work Site</li> </ul> <p>Workflow initiation via device scanning user interface (template selection at device UI) Adding of Metadata information</p>

*Continued*  
\*Features, configurations, and options vary by location

## Scan Specifications

NETWORK SCANNING SOFTWARE SOLUTIONS *(Continued)*

<b>SMARTsend*</b> <b>Professional (optional)</b>	Everything in SMARTsend, plus: <ul style="list-style-type: none"> <li>• Workflow initiation via Paperware (Scan coversheets)</li> <li>• Server-based Optical Character Recognition (OCR)</li> <li>• Searchable PDF</li> <li>• Scan to Internet fax file destination</li> <li>• TrueMatch patented search technology</li> </ul>
---	--

## Fax Specifications

FAX OPTIONS – Walk-up option *(One or Two Lines options)*

<b>Compatibility</b>	ITU (CCITT) Group 3
<b>Memory</b>	At least 32 MB (One Line) 256 MB (Two Line)
<b>Speed/Modem(s)</b>	1 or 2 V.34 modems: 33,600bps. Less than 4 seconds per page transmission time, ISDN via third party adapter
<b>Compression/Speed</b>	MH/MR/MMR/JBIG/G3/Super G3
<b>Fax Send Features</b>	Quality/Resolution <ul style="list-style-type: none"> <li>• Original type: Normal, text, half tone, photo, lighter/darker, background suppression</li> <li>• Fax - off Platen, mixed sizes or Bound/Book</li> </ul> Auto Send (Up to 5) Audio line monitor Transmission options (Report/Header) Reduce/Split large documents Cover letter Delayed send Build Job (up to 1000 images) Polling
<b>Fax Receive Features</b>	One or two-sided printing Stapled or unstapled, hole punch Receive print mode --Manual (size, margin, stock, header)/Auto Auto answer delay Secure receive Junk fax prevention
<b>Fax Reports</b>	Activity Dial directory Group directory Options Pending Jobs
<b>Fax Mailboxes</b>	Up to 100 password-protected Poll Remote mailboxes (up to 255) password-protected

*Continued*  
\*Features, configurations, and options vary by location

## Fax Specifications

FAX OPTIONS – Walk-up option (*One or Two Lines options*) (Continued)

<b>Auto Dialing Features</b>	Speed Dials	
	<ul style="list-style-type: none"> <li>• 200 (One-line option)</li> <li>• 1,000 (Two-line option)</li> </ul>	
	Group Dials	
	<ul style="list-style-type: none"> <li>• Up to 100 groups with up to 200 recipients per group (One-line option)</li> <li>• Up to 200 groups with up to 400 recipients per group (Two-line option)</li> </ul>	
	Auto redial	
	<ul style="list-style-type: none"> <li>• Up to 14 attempts</li> <li>• Up to 25 min intervals</li> <li>• Batch Send (up to memory capacity)</li> </ul>	
<b>Resolutions</b>	200 x 100 dpi (Standard)	400 x 400 dpi
	200 x 200 dpi (Fine)	400 x 600 dpi
	300 x 300 dpi	600 x 600 dpi (Super Fine)
	200 x 400 dpi	

FAX OPTIONS – LAN Fax with Walkup Fax (*Optional with the Copier/Printer*)

Driver based LAN fax for Windows and Macintosh users (PCL and PS drivers)  
 Recipient options (add recipient or add from phone book)  
 User personal phone book – up to 1,000 entries  
 Confirmation sheet  
 Send speed (14.4/33.6kbps or 4800bps)  
 Send time  
 Dialing options (prefix or credit card)  
 Cover sheet (add notes)  
 Preferences – Phonebook (personal or shared LDAP)

FAX OPTIONS – Internet Fax Enablement (*Standard; available with the Copier/Printer/Scanner only*)

<b>Capability</b>	Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP)
	Reception and automatic printout of documents sent via e-mail from remote Internet Fax machines or e-mail clients
<b>Maximum Scan Area</b>	11 x 17 in. (A3/297 x 420 mm)
<b>Address Directory Access</b>	Corporate address list via LDAPv3
	Downloaded address list (comma-separated file format)
	Internal LDAP or Public address book
<b>File Formats</b>	TIFF-FX profiles S, F with G3 MH or JPEG compression
	PDF (image only) with G3 MH, G4 MMR or JPEG compression
	PDF and Multi TIFF
<b>Resolutions</b>	600 x 600 dpi
	400 x 400 dpi
	300 x 300 dpi
	200 x 200 dpi
<b>Network Protocols</b>	SMTP
	POP3 (RFC 1939)
<b>Compliance</b>	ITU-T T.37 compliant

Continued

## Fax Specifications

FAX OPTIONS – Internet Fax Enablement (*Standard; available with the Copier/Printer/Scanner only*) (Continued)

<b>Features</b>	Signature (SA configurable – 16 lines each of 128 character max) Delivery Confirmation <ul style="list-style-type: none"> <li>• Email receipt option</li> <li>• Confirmation reply option</li> <li>• Cover sheet option</li> <li>• Subject (248 characters)</li> <li>• User configurable message body</li> </ul>
-----------------	---

FAX OPTIONS – Network Fax Server Enablement (*Standard; available with the Copier/Printer/Scanner only*)

<b>Capability</b>	Provides walk-up faxing and hard copy output of received faxes when integrated with fax server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration (via SMTP).
-------------------	---

<b>Maximum Scan Size</b>	11 x 17 in. (A3/297 x 420mm)
--------------------------	------------------------------

<b>Network Protocols</b>	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS SMTP
--------------------------	---

<b>Fax Send Features</b>	One- or two-sided scanning (up to 11 x 17 in. (A3/297 x 420 mm) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, lighten/darken, photo, background suppression, seven levels of contrast, seven levels of sharpness)
--------------------------	---

<b>Fax Print Features</b>	One – or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)
---------------------------	---

<b>Supported Network Fax Vendors</b>	Multiple vendors, certified by the Xerox Business Alliance Partner Program. For details visit <a href="http://www.xerox.com">www.xerox.com</a>
--------------------------------------	--

## Device Management Specifications

## ACCOUNTING FEATURES – Internal Auditor

<b>Tracking</b>	Copy usage
<b>Accounting</b>	Up to 2,150 User accounts Up to 5,925 General accounts Up to 256 Group accounts

Continued

---

**Device Management Specifications**
**ACCOUNTING FEATURES – Internal Auditor (Continued)**

**Features**                      Auditor report printout, ability to upload/download account and usage data via direct connection using Microsoft Windows based software

**ACCOUNTING FEATURES – Xerox Standard Accounting (Standard with the Copier/Printer and the Copier/Printer/Scanner)**

**Tracking**                      Copy, Print, Fax and Scan usage

**Accounting**                    Up to 2,500 User accounts (User Id)  
Up to 500 General accounts (Client)  
Up to 500 Group accounts (Department)

**Features**                      Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.

Xerox Standard Accounting can be used in conjunction with an external device via the FDI (e.g. Coin Op or Card Reader)

**ACCOUNTING OPTIONS – Network Accounting Enablement Kit (Optional)**

Enhanced network accounting with up to the minute data on how the WorkCentre system is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options available through Xerox Business Alliance Partner solutions. For details visit [www.xerox.com](http://www.xerox.com)

Security enhancements with the addition of HTTPS protocol support  
WorkCentre requests account authentication from 3rd party server enabling larger databases of users and accounts

**SECURITY – review the supplemental Security brochure for details**

**Authentication**                Secure device login with network user name and password  
Supports Kerberos (Windows 2000/UNIX/Windows Server 2003)  
SMB (Windows NT 4.0/Windows 2000/Windows Server 2003)  
Novell over IP/IPX (Novell NetWare 4.x/5.x/6.x)  
PIN-based guest login  
LDAP  
Secure Access

**Features**                      802.1x Compliant  
IPv6 Compliant  
Disk Image Overwrite – Immediate, On Demand, Scheduled  
HTTPS (SSL)  
SNMP V3  
IPSec  
Network Authentication  
Device Access Password Protection  
IP Filtering  
Audit Log  
Disk Encryption – for Store Print and Scan to Mailbox features on WorkCentre  
Secure Print  
Fax Security  
Image Overwrite (Immediate, On Demand and Scheduling)

Continued

## Device Management Specifications

### SECURITY – review the supplemental Security brochure for details

<b>Options</b>	Xerox Secure Access Unified ID System™ is a unique card based system that leverages an organization's existing ID infrastructure to provide secure access to Xerox devices.
<b>Common Criteria Certification</b>	Available Post Launch.

### XEROX EXTENSIBLE INTERFACE PLATFORM (EIP)

Xerox EIP is a development platform that allows customers, Xerox Business Partners and System Integrators to build unique applications that are presented at the WorkCentre 5600 series user interface. Xerox EIP is an open standard platform that utilizes industry standard development tools enabling applications that are easily developed and customized to meet the needs of any business environment or personalized for each user. These applications will yield simpler user interactions and result in less time interacting with the MFP which drives increased worker productivity and systems that easily adapt to your business processes.

## Machine Specifications

### MONTHLY DUTY CYCLE

5632 – up to 125,000 pages  
 5638 – up to 150,000 pages  
 5645 – up to 175,000 pages  
 5655 – up to 200,000 pages

### BASIC CONFIGURATIONS\*

WorkCentre with Platen, Two Trays and Stand (5632 only)  
 WorkCentre with DADF, Two Trays and Stand (5632, 5638, 5645 only)  
 WorkCentre with DADF, Two Trays, Stand and High Capacity Tandem Tray

### ACCESSORY OPTIONS\*

<b>Copier</b>	<ul style="list-style-type: none"> <li>Walkup Fax: One line and Two lines</li> <li>High Capacity Tandem Tray</li> <li>High Capacity Feeder</li> <li>Optional 8.5 x 11 / 8.5 x 14 Short Edge Kit for High Capacity Feeder</li> <li>Optional 11 x 17 Short Edge Kit for High Capacity Feeder</li> <li>Offset Catch Tray (OCT)</li> <li>Basic Office Finisher (available with 5632/5638/5645 only)</li> <li>Office Finisher</li> <li>Professional Finisher</li> <li>High Volume Finisher (available with 5655 only)</li> <li>High Volume Finisher with Booklet Maker (available with 5655 only)</li> <li>High Volume Finisher with Booklet Maker with Z-Fold / C-Fold unit and Post Process Inserter (available with 5655 only)</li> <li>Convenience Stapler</li> <li>Hole Punch (with Office Finisher and High Volume Finishers – see Output Options for details)</li> <li>Envelope Tray Kit (for Tray 2 position)</li> <li>256 MB Pre Collation Memory (EPC)</li> <li>Foreign Device Interface (FDI)</li> <li>Xerox Copier Assistant (XCA) (UK only)</li> <li>Upgrade Kit to Copier/Printer</li> <li>Upgrade Kit to Copier/Printer/Scanner (Includes Network Scanning, Scan to Email, Network Server Fax and Internet Fax)</li> </ul>
---------------	--

\*Features, configurations and options may vary by location *Continued.*

## Machine Specifications

## ACCESSORY OPTIONS\* (Continued)

<b>Copier/Printer</b>	Walkup Fax with LAN Fax: One line and Two lines USB 2.0 / (IEEE1284) Parallel Port Kit (Available with Copier/Printer/Scanner only) Scan to PC Desktop SE and Professional (Available with Copier/Printer/Scanner only) Xerox Unicode International Printing Kit Enablement for Network Accounting and Xerox Business Alliance Partner Solutions Upgrade Kit to Copier/Printer/Scanner (includes Network Scanning, Scan to Email, Network Server Fax and Internet Fax)
-----------------------	---

## ELECTRICAL REQUIREMENTS

110-140 Volt Nominal, 60 Hz, 15A (North America)  
 220-240 Volt Nominal, 50 Hz, 10A (Europe)  
 Note: Convenience Stapler requires separate 110V 15A circuit

POWER CONSUMPTION <sup>1</sup>	5632/5638 Copier <sup>1</sup>	5632/5638 Copier/Printer <sup>1</sup>	5645/5655 Copier <sup>1</sup>	5645/5655 Copier/Printer <sup>1</sup>
<b>Running</b>	≤ 1080 watts	≤ 1130 watts	≤ 1180/1280 watts	≤ 1280/1380 watts
<b>Standby</b>	≤ 265 watts	≤ 305 watts	≤ 265 watts	≤ 305 watts
<b>Low Power Mode</b>	≤ 100 watts	≤ 125 watts	≤ 100 watts	≤ 135 watts
<b>Auto Off / Sleep mode</b>	≤ 4 watts	≤ 9 watts	≤ 4 watts	≤ 9 watts
<b>Warm up to Copy</b>	≤ 28 seconds	≤ 28 seconds	≤ 28 seconds	≤ 28 seconds
<b>Ready to Print</b>	NA	≤ 130 seconds	NA	≤ 130 seconds
<b>Low Power Recovery</b>	≤ 9 seconds	≤ 9 seconds	≤ 9 seconds	≤ 9 seconds

## ENVIRONMENTAL CONSIDERATIONS

<b>Required Temperature Range</b>	10° to 32° C
<b>Required Relative Humidity</b>	10% to 85%

\*Features, configurations and options may vary by location. <sup>1</sup> With Office Finisher. *Continued*

## Machine Specifications

## DIMENSIONS AND WEIGHTS (Copier)

	Width <sup>2</sup>	Depth	Height	Weight <sup>1</sup>
<b>Configuration With OCT</b>	38 in. / 955 mm	26 in. / 650 mm	40 in./1,010 mm 45 in./1,140 mm	<b>Platen*/HCTT</b> 222 lbs/101 kg <b>DADF/HCTT</b> 264 lbs/120 kg
<b>With Basic Office Finisher</b>	48 in. / 1,214 mm	26 in. / 650 mm	40 in./1,010 mm 45 in./1,140 mm	<b>Platen/HCTT</b> 273 lbs/124 kg <b>DADF/HCTT</b> 315 lbs/143 kg
<b>With Office Finisher</b>	48 in. / 1,214 mm	26 in. / 650 mm	40 in./1,010 mm 45 in./1,140 mm	<b>Platen/HCTT</b> 282 lbs/128 kg <b>DADF/HCTT</b> 326 lbs/148 kg
<b>With Professional Finisher</b>	56 in. / 1,420 mm	26 in. / 650 mm	44 in./1,120 mm 45 in./1,140 mm	<b>Platen/HCTT</b> 388 lbs/176 kg <b>DADF/HCTT</b> 432 lbs/196 kg
<b>With High Volume Finisher (5655 Only)</b>	65 in. / 1,650 mm	26 in. / 650 mm	45 in./1,140 mm	<b>DADF/HCTT/HVF</b> 421 lbs/191 kg
<b>With High Volume Finisher with Booklet Maker (5655 Only)</b>	66 in. / 1,670 mm	26 in. / 650 mm	46 in./1,180 mm	<b>DADF/HCTT/HVFBM</b> 480 lbs/218 kg
<b>With High Volume Finisher with C/Z Folder and Post Process Inserter (5655 Only)</b>	80 in. / 2,030 mm	26 in. / 650 mm	46 in./1,180 mm	<b>DADF/HCTT/HVFBM/PPI</b> 548 lbs/249 kg
<b>High Capacity Feeder</b>	15 in. / 389 mm	20 in. / 510 mm	23 in. / 575 mm	66 lbs / 30 kg

## DIMENSIONS AND WEIGHTS (Copier/Printer)

	Width <sup>2</sup>	Depth	Height	Weight <sup>1</sup>
<b>Configuration With DADF and OCT</b>	49 in. / 1,240 mm	27 in. / 675 mm	45 in. / 1,140 mm	280 lbs / 127 k
<b>With DADF and Basic Office Finisher</b>	59 in. / 1,499 mm	27 in. / 675 mm	45 in. / 1,140 mm	330 lbs / 150 kg
<b>With DADF and Office Finisher</b>	59 in. / 1,499 mm	27 in. / 675 mm	45 in. / 1,140 mm	339 lbs / 154 kg
<b>With DADF and Professional Finisher</b>	67 in. / 1,705 mm	27 in. / 675 mm	45 in. / 1,140 mm	445 lbs / 202 kg
<b>With High Volume Finisher (5655 Only)</b>	76 in. / 1,935 mm	27 in. / 675 mm	45 in. / 1,140 mm	436 lbs / 198 kg
<b>With High Volume Finisher with Booklet Maker(5655 Only)</b>	77 in. / 1,955 mm	27 in. / 675 mm	46 in. / 1,180 mm	496 lbs / 225 kg
<b>With High Volume Finisher with C/Z Folder and Post Process Inserter (5655 Only)</b>	91 in. / 2,315 mm	27 in. / 675 mm	46 in. / 1,180 mm	564 lbs / 256 kg
<b>High Capacity Feeder</b>	15 in. / 389 mm	20 in. / 510 mm	23 in. / 575 mm	66 lbs / 30 kg

\*Available with 5632 only. <sup>1</sup> Weights do not include Shelf (2.99 lbs. / 1.36 kg). <sup>2</sup> Bypass Tray closed.

**Machine Specifications**

<b>NOISE LEVELS*</b>	<i>5632/5638 Copier</i>	<i>5645 Copier</i>	<i>5655 Copier</i>	<i>5632/5638 Copier/Printer</i>	<i>5645/5655 Copier/Printer</i>
<b>Standby dB (A) SPL</b>	32	35	35	32	35
<b>Run Continuous dB (A) SPL</b>	45	56	56	58	59
<b>Run Impulse dB (A) L SPL</b>	57	59	61	61	63

\*Noise levels shown are "Not to Exceed" levels. Actual noise levels will be lower.

**CERTIFICATIONS**

FCC Class A Compliant (US), DOC Class A Compliant (Canada)  
 89/336/EEC (Europe)  
 UL Listed (UL 1950, Third Edition)  
 CB Certified (IEC 60950/EN 60950)  
 73/23/EEC (Europe)  
 95/5/EEC (Europe)  
 Energy Star

<b>SUPPLIES</b>	<b>Description</b>	<b>Order Number</b>	<b>No. per Box</b>	<b>Expected Yield</b>
	Toner Cartridge	006R1046	2	>32,000 at 6% area coverage per bottle
	Waste Toner Bottle (supplied with each toner cartridge box)	008R12896	1	100,000
	Staple Cartridge / Pack (for Basic Office Finisher)	108R00682 108R00535	1 3	3,000 per cartridge 3,000 per cartridge (9,000 staples)
	Staple Cartridge (for Office Finisher)	108R00493	3	5,000 per cartridge (15,000 staples)
	Staple Cartridge (for Professional Finisher and HVF with Booklet Maker - saddle-stitch stapling)	008R12897	8 (4 x 2)	2,000 per cartridge (16,000 staples)
	Staple Cartridge (for Convenience Stapler)			
	• Complete Cartridge	008R12964	1	5,000 per cartridge
	• Refill Cartridge	008R12941	3	5,000 per cartridge (15,000 staples)
	Staple Cartridge (for HVF and HVF with Booklet Maker)	008R12912	1	5,000 per cartridge

## Machine Specifications

## SMart Kits

<i>Description</i>	<i>Order Number</i>	<i>No. per Box</i>	<i>Expected Yield</i>
Fuser Module (includes ozone filter)	109R00752 (N. America)	1	400,000
	109R00751 (Europe)	1	400,000
Xerographic Module - Metered (5632/5638)	113R00608	1	200,000
Xerographic Module - Metered (5645/5655)	113R00672	1	400,000
Xerographic Module - Sold (5632/5638)	113R00610 (N. America)	1	200,000
	113R00607 (Europe)		
Xerographic Module - Sold (5645/5655)	113R00674 (N. America)	1	400,000
	113R00673 (Europe)		
Document Handler Feeder Rolls (5632/5638)	113R00717	1	150,000 feed
Document Handler Feeder Rolls (5645/5655)	113R00718	1	150,000 feed



© 2007 Xerox Corporation. All rights reserved. XEROX®, CentreWare®, WorkCentre® and Copier Assistant are trademarks of Xerox Corporation in the United States and/or other countries. PostScript is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. Other marks are trademarks or registered trademarks of the companies with which they are associated. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. ENERGY STAR® is a U.S. registered mark. As an ENERGY STAR® Partner, Xerox Corporation has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. Product information and/or specifications are subject to change without notice. 11/07 610P727800B W56SS-01UC